

Project Name

Location

Prepared By



SATCO S39977

15T8/LED/48-840/DR

Notes

General

| | |
|------------------------|--|
| Status | Active |
| Watts | 15 |
| Fluorescent Equivalent | 25-32 |
| Volts | 120V-277V |
| Ballast Type | Type A |
| Shape | T8 |
| Base | Medium Bi Pin |
| ANSI Base | G13 |
| Nominal Length | 48 |
| Finish | Gloss White |
| CCT (Kelvin) | 4000 |
| Temperature | Cool White |
| CRI | 82 |
| Lumens | 2200 |
| Beam Spread | 210 |
| Dimmable | Check Ballast MFG for Dimmer Compatibility |
| Hours Rated | 50000 |
| Lamp Type | Linear |
| Technology | LED |

Electrical

| | |
|-------------------------|--|
| Ballasting Requirements | Ballast required. Direct Replacement - for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart |
| Power Factor | 0.9 |
| Operating Temperature | -20C (-4F) to a maximum of +45C (+113F) |

Physical

| | |
|-----|----|
| MOL | 48 |
| MOD | 1 |

Additional Information

| | |
|----------|-------------------------------|
| Warranty | 5 Year Limited - T8 LED Bulbs |
|----------|-------------------------------|

Compliance

| | |
|-----------------|-------------------------------|
| Safety Listing | cULus |
| Location Rating | Damp |
| Energy Star | No |
| DLC Approved | Yes |
| DLC ID | PL3A7LM1DMBQ |
| CEC Status | Lawful for sale in California |
| RoHS Compliant | Yes |
| NSF Approved | Yes - Approved |

